



LOW-CURRENT LED LAMPS (ROUND TYPES)

Package	Part No.	Chip		Lens Appearance	Absolute Maximum Ratings			Electro-optical Data (At 2mA)			Viewing Angle 2q 1/2 (deg)	Drawing No.
		Material/Emitted Color	Peak Wave Length λp (nm)		Dl (nm)	Pd (mw)	If (mA)	Vf (V)		Iv (mcd)		
								Typ	Max	Typ.		
T-1 Standard 1.0" Lead 3 φ	BL-B5141-L	GaP/GaP/Bright Red	700	Red Diffused	90	14	7	1.9	2.2	1.0	35	L-060
	BL-B4541-L	GaAsP/GaP/Hi-Eff Red	635		45	14	7	1.8	2.2	4.0		
	BL-B2141-L	GaP/GaP/Green	568	Green Diffused	30	14	7	1.9	2.2	4.0		
	BL-BX1141-L	GaP/GaP/Hi-Eff Green	568		30	14	7	1.8	2.2	7.0		
	BL-B3141-L	GaAsP/GaP/Yellow	585	Yellow Diffused	35	14	7	1.9	2.2	3.0		
	BL-B4141-L	GaAsP/GaP/Orange	635	Orange Diffused	45	14	7	1.8	2.2	4.0		
	BL-B4341-L	GaAsP/GaP/Orange	635	Water Clear	45	14	7	1.8	2.2	12.0	30	
T-1 1.0" Lead 3 φ	BL-B45V1G-L	GaAsP/GaP/Hi-Eff Red	635	Red Diffused	45	14	7	1.8	2.2	4.0	35	L-061
	BL-B21V1G-L	GaP/GaP/Green	568	Green Diffused	30	14	7	1.9	2.2	4.0		
	BL-B31VG-L	GaAsP/GaP/Yellow	585	Yellow Diffused	35	14	7	1.9	2.2	3.0		
	BL-B24V1G-L	GaP/GaP/Green	568	Green Trans	30	14	7	1.9	2.2	8.0	30	
	BL-B34VG-L	GaAsP/GaP/Yellow	585	Yellow Trans	35	14	7	1.9	2.2	6.5		
	BL-B23V1G-L	GaP/GaP/Green	568	Water Clear	30	14	7	1.9	2.2	8.0		
	BL-B33V1G-L	GaAsP/GaP/Yellow	585		35	14	7	1.9	2.2	6.5		
1.0" Lead High Flangeless 3 φ	BL-B45V1H-L	GaAsP/GaP/Hi-Eff Red	635	Red Diffused	45	14	7	1.8	2.2	4.0	30	L-062
	BL-B21V1H-L	GaP/GaP/Green	568	Green Diffused	30	14	7	1.9	2.2	5.0		
	BL-B31V1H-L	GaAsP/GaP/Yellow	585	Yellow Diffused	35	14	7	1.9	2.2	3.0		
	BL-B24V1H-L	GaP/GaP/Green	568	Green Trans	30	14	7	1.9	2.2	10.0	25	
	BL-B34V1H-L	GaAsP/GaP/Yellow	585	Yellow Trans	35	14	7	1.9	2.2	6.0		
	BL-B23V1H-L	GaP/GaP/Green	568	Water Clear	30	14	7	1.9	2.2	10.0		
	BL-B33V1H-L	GaAsP/GaP/Yellow	585		35	14	7	1.9	2.2	6.0		
T-13/4 Standard 1.0" Lead 5 φ	BL-B5134-L	GaP/GaP/Bright Red	700	Red Diffused	90	14	7	1.9	2.2	1.2	35	L-063
	BL-B4534-L	GaAsP/GaP/Hi-Eff Red	635		45	14	7	1.8	2.2	8.0		
	BL-B2134-L	GaP/GaP/Green	568	Green Diffused	30	14	7	1.9	2.2	8.0		
	BL-BX1134-L	GaP/GaP/Hi-Eff Green	568		30	14	7	1.8	2.2	12.5		
	BL-B3134-L	GaAsP/GaP/Yellow	585	Yellow Diffused	35	14	7	1.9	2.2	7.0		
	BL-B4134-L	GaAsP/GaP/Orange	635	Orange Diffused	45	14	7	1.8	2.2	8.0		
	BL-B4334-L	GaAsP/GaP/Orange	635	Water Clear	45	14	7	1.8	2.2	20.0	12	
T-13/4 Standard 1.0" Lead 5 φ	BL-B5134G-1-L	GaP/GaP/Bright Red	700	Red Diffused	90	14	7	1.9	2.2	0.8	45	L-064
	BL-B4534G-1-L	GaAsP/GaP/Hi-Eff Red	635		45	14	7	1.8	2.2	6.5		
	BL-B2134G-1-L	GaP/GaP/Green	568	Green Diffused	30	14	7	1.9	2.2	6.5		
	BL-BX1134G-1-L	GaP/GaP/Hi-Eff Green	568		30	14	7	1.9	2.2	10.5		
	BL-B3134G-1-L	GaAsP/GaP/Yellow	585	Yellow Diffused	35	14	7	1.9	2.2	5.5		
	BL-B4334G-1-L	GaAsP/GaP/Orange	635	Water Clear	45	14	7	1.8	2.2	16.0	20	
T-13/4 Flangeless 1.0" Lead 5 φ	BL-B5134N-1-L	GaP/GaP/Bright Red	700	Red Diffused	90	14	7	1.9	2.2	0.9	45	L-065
	BL-B4534N-1-L	GaAsP/GaP/Hi-Eff Red	635		45	14	7	1.8	2.2	7.0		
	BL-B2134N-1-L	GaP/GaP/Green	568	Green Diffused	30	14	7	1.9	2.2	7.0		
	BL-BX1134N-1-L	GaP/GaP/Hi-Eff Green	568		30	14	7	1.8	2.2	11.2		
	BL-B3134N-1-L	GaAsP/GaP/Yellow	585	Yellow Diffused	35	14	7	1.9	2.2	6.5		

Remark: 1. Hi-Eff Red/High-Efficiency Red.

2. Trans/Transparent.

3. 2 θ 1/2 The off-axis angle at which the luminous intensity is half the axial luminous intensity.



STANDARD LED LAMPS (ROUND TYPES)

<p>L-060 BL-Bxx41-L Series</p>	<p>L-061 BL-BxxV1G-L Series</p>
<p>L-062 BL-BxxV1H-L Series</p>	<p>L-063 BL-Bxx34-L Series</p>
<p>L-064 BL-Bxx34G-1-L Series</p>	<p>L-065 BL-Bxx34N-1-L Series</p>

- Notes: 1. All Dimensions are in millimeters (inches).
2. Tolerance is $\pm 0.25\text{mm}$ (.010")